

PROFESSIONAL CONDENSATION DEHUMIDIFIERS

DH 752-DH 792



DH 752



DH 792



- Automatic fast defrosting using hot gases
- High efficiency
- Durable casing
- Simple operation
- Built-in hygostat
- Continuous operation possible (24 h/day)
- Water tank with automatic shut-off when full
- Possibility to connect a hose to remove condensed water
- Hour counter
- Air filter

DRYING

Optional accessories



Water pump for DH 752 and DH 792
Max. forcing height - 4m
4512.442

Condensation dehumidifiers condense the water from the air using a cold surface.



Specifications	Units	DH 752	DH 792
Capacity (30°C/80% RH)	l/24h	45.6	100
Capacity (20°C/60% RH)	l/24h	20.3	44.6
For rooms of approx.	m ³	701	1500
For restoration after flood	m ³	280	600
Refrigerant		R290	R454C
Air flow	m ³ /h	350	1,000
Operating temperature range	°C	5-35	5-32
Operating humidity range	%	20-90	35-90
Power consumption	W	900	1,840
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50
Sound level	dB(A)	52	69
Compressor		Rotary	Rotary
Tank capacity	l	5.7	15
Product size (l x w x h)	mm	580 x 422 x 820	620 x 540 x 1095
Box size (l x w x h)	mm	610 x 405 x 660	730 x 526 x 1150
Net/gross weight	kg	30/36	64/70
Pallet	pcs	12	2